



## SSW Horizontal Pipeline Centrifugal Sea Water Pump



### Product Overview

SSW stainless steel centrifugal pump product overview in strict accordance with the international standard ISO2858 and the newer national pipeline centrifugal pump standard /T53A52-93 design and manufacture of energy-efficient products. The pump adopts domestic advanced hydraulic model optimization design.

### Feature

1. Smooth operation: pump shaft concentric impeller excellent dynamic and static balance, to ensure smooth operation, no vibration,
2. Watertight: mechanical seals of different materials ensure that there is no leakage in the transmission of different media.
3. Low noise: two low noise bearings under the pump, smooth operation, in addition to the motor weak sound, basically no noise.
4. Low failure rate: simple and reasonable structure, the key parts of the quality supporting, the whole machine trouble-free working time greatly improved.
5. Easy maintenance: replace seals, bearings, simple and convenient.
6. Covers more province: the exit can be left, right, upward three directions, easy to install the pipeline layout, save space

### Performance Table

Model	Flow(m <sup>3</sup> /h)	Head(m)	Rate power (kW)	Rated voltage (v)	Inlet and outlet(mm)
SSW-100S-4KW	120	22	4	380	100
SSW-100S-5.5KW	135	26	5.5	380	100
SSW-150S-5.5KW	145	24	5.5	380	150
SSW-100S-7.5KW	155	30	7.5	380	100
SSW-150S-7.5KW	165	28	7.5	380	150
SSW-100S-11KW	165	35	11	380	100
SSW-150S-11KW	175	33	11	380	150
SSW-100S-15KW	175	40	15	380	100
SSW-150S-15KW	185	38	15	380	150